

Environmental Meters

\$225
LM-8000



Model LM-8000

Anemometer, humidity meter, light meter and a Type K digital thermometer in one unit.

- Light: 0 to 20,000 Lux / 0 to 2,000 Ft-cd, auto ranging
- Anemometer: 80 to 5900 fpm
- Velocity Units: m/s, km/h, mph, knots, ft/min
- Type K Thermometer: -100 to 1300°C
- User selectable °C/°F, Lux/Foot-candles
- Humidity: 10 to 95%RH
- Data Hold, Record (Max/Min)
- Compact & lightweight
- Includes battery

Optional Accessories:

Model CA-52A Soft Carrying Case Price \$15

\$295
ST-8820



Model ST-8820

4-in-1...Sound, light, humidity and temperature functions in one meter.

- Sound level function can be used to measure noise levels in factories, schools, offices, studios & auditoriums
- Sound Level Range: 35 to 135 dB, A low/high & C low/high
- Light function is used to measure luminance in the field
- The light sensitive component used is a silicon diode & is fully cosine corrected for the angular incidence of light
- Light Range: 0.01 to 20,000 lux
- Semiconductor humidity sensor
- Type K thermocouple temperature input
- Data Hold & Max Hold
- Auto shut off & low battery indication
- Included accessories: K-type thermocouple probe, carrying case & 9V battery

\$115
ST-22



Model ST-22

An ideal instrument with scores of practical applications for professional and home use.

- 4-in-1 high performance multi-tester
- Light Function: 20,000 Lux, Sound to 100 dB, & Humidity to 95%RH
- Temperature Range to 1300°C
- Auto shut off & low battery indication
- Included accessories: K-type temperature probe, rubber holster & 9V battery

Optional Accessories:

Model CA-03 Soft Carrying Case Price \$18

LM-8000	ST-8820	ST-22
10 to 95% RH	25 to 95% RH	25 to 95% RH
0.1% RH	0.1% RH	0.1% RH
±4% RH	±5% RH	±5% RH
32 to 122°F/0 to 50°C (ambient)	-4 to 1400°F/-20 to 750°C	-4 to 2300°F/-20 to 1300°C
0.1°F/°C	0.1° ≤ 200°, 1° > 200°	0.1° ≤ 200°, 1° > 200°
±1% of reading	±3% of reading	±3% of reading
Dual LCD	LCD	LCD
1 x 9V battery	1 x 9V battery	1 x 9V battery
6.1 x 2.4 x 1.3"/156 x 60 x 33 mm	9.9 x 2.5 x 1.6"/251 x 64 x 40 mm	4.75 x 2.4 x 1.6"/121 x 61 x 40 mm
5.6 oz/160 g	8.8 oz/250 g	9.9 oz/280 g
\$225	\$295	\$115