

# Multimeter Accessories



**\$23**  
**581**

## Model 581

### Safety Test Leads.

The tip on this lead is made of .080" dia. x 1/2" long brass tip threaded 8-32 for attachments (nickel plated). The probe is molded flame retardant ABS plastic with a 3/4" safety ring. The wire is 18 ga. (65 x 36) tinned copper stranding, rubber insulation .145" dia. 20kV breakdown, 5kV working. Standard length is 4 feet. Sold as sets (1 red, 1 black).

#### Features:

- Rated 1000V, 10A
- Tapered strain relief
- Brass tip, 8-32 threads
- Probe is molded flame retardant ABS plastic with a 3/4" safety ring



**\$22**  
**582**

## Model 582

### Safety Test Leads.

The tip on this lead is made of .080" dia. x 1/2" long brass tip threaded 8-32 for attachments (nickel plated). The probe is molded flame retardant ABS plastic with a 3/4" safety ring. The wire is 18 ga. (65 x 36) tinned copper stranding, rubber insulation .145" dia. 20kV breakdown, 5kV working. Standard length is 4 feet. Sold as sets (1 red, 1 black).

#### Features:

- Rated 1000V, 10A
- Tapered strain relief
- Brass tip, 8-32 threads
- Probe is molded flame retardant ABS plastic with a 3/4" safety ring



**\$22**  
**518-6**

## Model 518-6

### Safety Test Leads.

The tip on this lead is made of .080" dia. x 5/8" long stainless steel with polished tip for insulation piercing. Threaded 8-32 for attachments (nickel plated). The probe is molded flame retardant ABS plastic with a 3/4" safety ring. The wire is 18 ga. (65 x 36) tinned copper stranding, rubber insulation .145" dia. 20kV breakdown, 5kV working. Standard length is 4 feet, sold as sets (1 red, 1 black)



**\$9**  
**833**

## Model 833

### Multi Mini Clip Lead Set.

A good quality lead for an economical price. Includes 2 each of five different coloured, 24-ga. wire, 3 feet long, with clips & boots on both ends.



**\$4**  
**458-1**

## Model 458-1

### Threaded Alligator Clip.

This 8-32 threaded clip attaches directly onto any test lead probe tip with matching threads & allows the user to attach the lead to any wire or terminal.

Material: Steel, cadmium plated, threaded 8-32, PVC boot. Sold as sets (1 red, 1 black).



**\$10**  
**497-3**

## Model 497-3

### Threaded Hook-it.

Attaches directly onto any test lead probe tip with matching threads, & allows the user to attach lead to any small connector.

Material: .028" dia. silver coated beryllium wire with brass nickel plate insert & nylon housing. Sold as sets (1 red, 1 black).

# Multimeter Accessories

**\$20**  
**AC-006**



**Model AC-006**

### AC Line Splitter.

- Enables clamp meter user to measure AC current on a 2-wire or 3-wire power cord to 15A
- Provides easy & safe measurements of current without the need to cut off the plug & separate the conductors
- Plugging the power connector into the Line Splitter separates the hot/live conductor from the neutral & ground
- Voltage check function
- Dimensions: 5.2 x 2 x 1"/133 x 51 x 25mm
- Weight: 5.8 oz/164 g

**\$12**  
**AD-1**



**Model AD-1**

### Input Adapter.

- Converts a type K probe with a mini connector to standard 3/4" banana jacks

**\$18**  
**CA-03**

**\$21**  
**CA-05A**

**\$15**  
**CA-52A**

Model CA-03



Model CA-05A



Model CA-52A



### Model CA-03, CA-05A & CA-52A

#### Carrying Cases.

- Protect & store your multimeter & accessories in a fabric carrying case

#### Model CA-03

Dimensions: 8 x 4.75 x 2.5" (205 x 120 x 64mm) (approx.)

#### Model CA-05A

Dimensions: 8 x 5.25 x 2.5" (250 x 130 x 65mm) (approx.)

#### Model CA-52A

Dimensions: 8 x 3.5 x 2.25" (205 x 90 x 57mm) (approx.)

**\$78**  
**LS-109**

**\$88**  
**LS-139**

**\$98**  
**LS-104**

**\$88**  
**LS-103**

**\$78**  
**LS-107**

**\$78**  
**LS-134A**



### Series LS

#### Type K Thermocouple Probes.

**Model LS-109** Surface Probe, K-type, Ribbon style (752°F/400°C max.) Price \$78

**Model LS-139** Surface Probe, K-type, Spring-loaded tip (932°F/500°C max.) Price \$88

**Model LS-104** Surface Probe, K-type, Right angle style (752°F/400°C max.) Price \$98

**Model LS-103** Air/Gas Probe, K-type (1472°F/800°C max.) Price \$88

**Model LS-107** General Purpose Immersion Probe, K-type (1292°F/700°C max.) Price \$78

**Model LS-134A** Needle Tip Penetration Probe, K-type (1472°F/800°C max.) Price \$78

**Model TP-01** Naked Bead Probe, K-type (500°F/260°C max.) Price \$19